







B6000

Gesamtgewicht	900 g/m ²		
Zusammensetzung	PES + PVC		
Gewebe	PES, 1100 dtex PES, 1100 dtex		
Lackierung -	Top: glossy Back: glossy	7999 300 cm	9002 300 cm
Höchstzugkraft	4000 N/5cm 4000 N/5cm		
Weiterreisskraft	600 N 500 N		
Haftung	100 N/5cm	1003 - RAL 1014 300 cm	1021 - RAL 1021 300 cm
Temperaturbeständigkeit	-40/+70 °C		
Lichtechtheid	7-8		
Brennverhalten	(ISO 3795 1989) < 100 mm/min		
		1024 - RAL 1003 300 cm	1059 - RAL 1032 300 cm

Andere Farben auf Anfrage

						
3002 300 cm	3015 - RAL 3002 300 cm	3017 300 cm	3018 300 cm	3056 300 cm		
						
5004 - RAL 5013 300 cm	5007 300 cm	5031 - RAL 5010 300 cm	5063 - RAL 5002 300 cm	6001 300 cm	6002 - RAL 6001 300 cm	
						
7001 300 cm	7002 - RAL 7035 300 cm	7024 300 cm	7244 - RAL 7043 300 cm		7500 - Silber 300 cm, 320 cm	